Declaration of Performance

Ref.: ZK-T-T/02/06



1. Type of product for identification: ceramic tiles, dry pressed

GLAZED INDOOR FLOOR TILES

type of product	nominal size (cm)	
ZBP, ZZP, ZPD letters (1-999)+ maximum 5 numbers	20x20,30x30, 45x45, 20x60, 20x50	
(30 000 – 99 999)		
KBX or KBK or KBR + 19xx – 2xxx year/number (1-999)		
Fantasy name		
decor elements with fancy name	special	

2. Proposed field of utilization:

covering inside wall and floor surfaces not exposed to freezing

3. Producer:

Zalakerámia Zártkörűen Működő Részvénytársaság, H-8946 Tófej, Rákóczi u. 44.

TEL: (36) 92/566-400, FAX: (36) 369-070 Info: (36) 80/34-34-34,

E-mail: info@zalakeramia.hu, web: www.zalakeramia.hu

4. System of assessment and verification of constancy of performance as set ou in Annex V.: System 4

Performance according to declaration:

5. Performance according to decla	ration:	
essential characteristics	performance	technical specification
water absorbtion	E>10%	EN 14411: 2016 group BIII annex L
bending strength	≥ 15 N/mm ²	EN 14411: 2016 group BIII annex L
•	$\geq 12 \text{ N/mm}^2$	
breaking strength		EN 14411: 2016 group BIII annex L
thickness ≥7,5 mm	≥ 600 N	
thickness < 7,5 mm	≥ 200 N	
reaction to fire	A1	without testing, 96/603/EC
frost resistance	not required	EN 14411: 2016 group BIII annex L
thermal shock resistance	as per norm	EN 14411: 2016 group BIII annex L
adhesion	with bonding cement: 0.5 N/mm ²	EN 14411: 2016 group BIII annex L
	with dispersion adhesives: 1.0 N/mm ²	
	with reactive resin adhesives: 2.0 N/mm ²	
slip reisistance	NPD	DIN 51 130, DIN 51 097
wear resistance	indicated by manufacturer (PEI 2,3,4,5)	ISO 10545-7
	indicated on packing	
durability	as per norm	PTK.6.169§(2) bekezdés
size and quality of surface	as per norm	EN 14411: 2016 group BIII annex L
resistance against staining agents		EN 14411: 2016 group BIII annex L
(class)	min.3	
cemical resistance (class)		
against low concentrate acids and	GLA	
alkalis		
against high concentrate acids and	NPD	EN 14411: 2016 group BIII annex L
alkalis		
househod chemicals and swimming	min. GB	
pool additives		
release of hazardous substances		EN 14411: 2016 group BIII annex L
- cadmium	as per norm	
- lead	as per norm	

- 6. The performance of the product identified in point 1 is in conformity with the declared performance in point 5.
- 7. First standard test: Accredited Test Laboratory of Építésügyi Minőségellenőrző Innovációs (ÉMI) Kht. (Non-profitCompany for Quality Control and Innovation in Building), 2000 Szentendre, Dózsa György út

FC-A137K-16358-2018 TVB: M-4062/2006-2011

8. The performance declaration has been issued in compliance with the requirements specified in the Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in ZALAKERÁMIA Zártkörűen Működő

Signed for and on behalf of the manufacturer by:

Részvénytársaság

8946 Tófej, Rákóczi út 44. Dr. Jaramani Rafik

Hadnagy Zoltán Financial director

Tófej, 2023.08.21

Chairman and CEO